



LASERSTAR CNC WELDING WORKSTATION

7902 Series



★ HIGHLIGHTS

- ✓ Robust Industrial Open Worktable Design
- ✓ Precision 3 Axis Coordinated MotionFX® Hardware
- ✓ Advanced MotionFX® Integrated Software
- ✓ Operating Modes: Manual, CNC, Teach Mode
- ✓ 80 & 150 Watts / Peak Power: 11kW

★ Mult-Axis Joystick with Fire Button Control Logic

★ Various Microscope Options Available

★ MotionFX® CNC X/Y/Z-Rotary Integrated System

- ✓ Includes Removable Axis Device
- ✓ Manual, Semi, & Full Automatic Modes
- ✓ Teach-Mode Enabled
- ✓ Joystick with Fire Button Control Logic
- ✓ Programmable Touch Screen Display
- ✓ High Accuracy X/Y/Z Axis Speed Control
- ✓ Includes Removable Rotary Device

★ Tilting Optical Beam Path Head

★ Pulse Performance Profile® (P³) Shaping Technology



A Must for All Welding Workshops



Ideal for Large Plastic Injection Mold Shops



Tool & Die / Mold Repair Maintenance



Repair Slots, Pockets, Contours & Angles



Repair Polished, Textured, Engraved Surfaces



Parting Line Edges & Heat Sensitive Areas



Tool Steel, Aluminum, Copper, Titanium, etc.



Pulse
Performance
Profile Technology®



LASERSTAR ACADEMY™

Our education courses are designed to provide you with a solid foundation of fundamental laser skill sets to immediately gain a revenue impact with your new laser device.

LaserStarAcademy.com

Technical Specifications at www.LaserStar.net

LASERSTAR CNC WELDING WORKSTATION

7902 Series



Laser Source	Nd: YAG
Operator Mode	Pulse
Output Power (Watts)	80W & 150W
Pulse Frequency	0.5 - 50 Hz
Beam Diameter	0.05 - 2.00mm
X-Y-Z Axis Travel	175mm x 100mm x 150mm
Max Load	50 kg (110 lbs.)
XY Resolution (µm)	12.5 microns
Accuracy (Linear Axis Only)	+/- (25 microns) per 25mm of travel
Speed (mm/sec)	15mm/sec
Software	CNC MotionFX® w/ Teach-Mode & Manual
Joystick	Direct Axis Control, Fire Button
Cooling Capacity	Internal Water-To-Air
Shielding Gas/Compress Air	Dual - Integrated "Soft Flow" Nozzle
Weight	Approx. 1140 lbs./517KG
Pedestal Dimensions*	50.5"L x 44.5"W x 66"H / 128cm x 113cm x 167cm
Supply Circuit	208-240 V, 50/60Hz, Single Phase
Laser Safety Compliance	FDA (CDRH), CSA, CE

* Motion in lowest/center positions, actual size changes based on position of the axis.

The LaserStar's 7902 Series state of the art, joystick-controlled, 3 axis manual laser welding system equipped with LaserStar's MotionFX® G-code programming software.

Dual operator logic allows for system control via the Joystick and/or Multi-Purpose Touch Screen Display.

The open workspace design is ideal for a wide range of component assembly and welding repair applications including plastic injection molds, dies and tooling repair, complex pressure sensitive hermetic laser sealing, and other unique industrial applications.



LASERSTAR.NET

MOTIONFX®



LASERSTAR.NET



LASERSTAR ACADEMY

LASERSTARACADMEY.NET



LASERSTARTV™

LASERSTAR.TV

LASERSTAR TECHNOLOGIES CORPORATION
2461 Orlando Central Parkway Orlando, Florida 32809 USA
Phone: +1-407-248-1142 ★ Email: sales@laserstar.net