

INDUSTRIAL EXHAUST SYSTEM

LASERSTAR[®]
TECHNOLOGIES

★ HIGHLIGHTS

- ✓ Compact, Robust Industrial Design
- ✓ Top Rated CFM: 225 WC: 35"
- ✓ HEPA & Odor Filters Included
- ✓ Supply Circuit: 120V & 230V
- ✓ Adjustable Circuit: 120V & 230V

- ★ Designed for Large Heavy Particles
- ★ Standard HEPA Filter Captures 99.97% of Fine Particles
- ★ Odor Filter Removes Most Fumes
- ★ Brushless High Speed Turbine Fumes
- ★ Easy Disposable Bag Filters Capture All Particles and Precious Metals for Easy Refining
- ★ Excellent for Continuous Usage
- ★ Interchangeable (Top or Side) Intake Plate
- ★ Optional Cyclone Attachment Available



Shown: Industrial Exhaust Unit
PN 648-249-15

- ✓ Usable with Most LaserStar Laser Systems
- ✓ Marking, Cutting, and Welding Systems Viable
- ✓ 6 Foot / 2 Meter Hose
- ✓ Optional: Cyclone Attachment (See Back)
- ✓ Brushless Engine
- ✓ Ideal for All Laser Environments
- ✓ 1 Year Warranty



LASERSTAR[®]
ACADEMY™

Our education courses are designed to provide you with a solid foundation of fundamental laser skill sets to immediately gain a revenue impact with your new laser device.

LaserStarAcademy.com

Technical Specifications at www.LaserStar.net

Engine	Brushless
Speed	Variable Adjustment
HEPA Filter	Standard
Odor Filter	Standard
Hose Length	6ft / 2m
Intake Plate	Top or Side Position
Service Indicators	Standard
Supply Circuit	120V or 230V
Warranty	One Year



Shown: Industrial Exhaust Unit & Cyclone
PN 648-249-15C

Industrial Exhaust Systems are compatible with many of Laserstar's laser welding, cutting and marking/engraving systems. It's robust, industrial design helps in the removal of harmful dust, gas fumes, and by-products of the lasing process while ensuring a safe environment for operators.

Added benefits of using a LaserStar exhaust system include reducing the particle buildup inside the laser system chamber, keeping critical optics dust free, capturing cover gases used, and maintaining your warranty requirements.

The LaserStar Industrial Exhaust System provides a communication interface cable which allows the exhaust unit to turn ON and OFF during the lasing process. The system also provides easy to replace dual bag filters allowing for longer run time between consumable replacements. Systems are available in a 120V or 230V model.



LASERSTAR.NET



LASERSTAR.NET



LASERSTAR
ACADEMY

LASERSTARACADEMY.NET



LASERSTARTV

LASERSTAR.TV

LASERSTAR TECHNOLOGIES CORPORATION

2461 Orlando Central Parkway Orlando, Florida 32809 USA

Phone: +1-407-248-1142 ★ Email: sales@laserstar.net