

FIBERSTAR® CNC WELDING WORKSTATION

8803 Series

★ **HIGHLIGHTS**

- ✓ Robust Industrial Open Workspace Design
- ✓ 3 Axis Coordinated MotionFX® Hardware
- ✓ Advanced MotionFX® Integrated Software
- ✓ Operating Modes: Manual, CNC, Teach Mode
- ✓ 150, 300, 450 & 600 Watt Models



*Tilting Optical Beam
Path Head*

★ **Portable Joystick Control with Fire Button Control Logic**★ **Sturdy Work Table w/ Z Axis Adjustment**

(Max Part Weight 200 lbs / 91 kg)

★ **MotionFX® Full CNC X/Y/Z Integrated System**

- ✓ Manual, Semi, & Full Automatic Modes
- ✓ Teach-Mode Enabled
- ✓ Joystick with Fire Button Control Logic
- ✓ Motion-Control Touchscreen
- ✓ High Accuracy X/Y/Z Axis Controller
- ✓ Optional Rotary Device

★ **Telescoping Laser Rail Assembly**★ **Integrated Windows PC with MotionFX™ Software**★ **Tilting Optical Beam Path Head (Optional)**

A Must for All Welding Workshops



Ideal for Large Plastic Injection Mold Shops



Tool & Die / Mold Repair Maintenance



Repair Slots, Pockets, Radius Contours & Angles



Repair Polished, Textured, Engraved Surfaces



Parting Line Edges & Heat Sensitive Areas



Tool Steel, Aluminum, Copper, Titanium, etc.



**LASERSTAR
ACADEMY™**

Our education courses are designed to provide you with a solid foundation of fundamental laser skill sets to immediately gain a revenue impact with your new laser device.

LaserStarAcademy.com

Technical Specifications at www.LaserStar.net

Laser Source	1070nm Ytterbium Fiber Engine
Operator Mode	Pulse or Continuous Wave (CW)
Average & Peak Power	150W (1.5kW) / 300W (3.0kW) 450W (4.5kW) / 600W (6.0kW)
Pulse Frequency	0Hz (Single-Shot Fire), 0.5-50Hz
Minimum Spot Size	>25 microns (configuration dependent)
X-Y Axis, Table Lift Column Travel	250mm x 250mm x 200mm
Max Load	200lbs (91kg)
XY Resolution (μm)	12.5 microns
Accuracy (Linear Axis Only)	+/- (25 microns) per 25mm of travel
Speed (mm/sec)	15mm/sec
Software	CNC MotionFX® w/ Teach-Mode & Manual
Joystick	Direct Axis Control, Fire Button
Cooling Capacity	Internal Forced Air / 24 hr Continuous Run Time
Shielding Gas/Compress Air	Integrated "Soft Flow" Nozzle
Supply Circuit	208-240V, 50/60Hz, Single Phase
Laser Safety Compliance	FDA(CDRH), CSA, CE

The **FiberStar 8803 series** is a state of the art, joy stick controlled, 3 axis laser welding system equipped with LaserStar's **MotionFX** G-code programing software.

The open workspace design is ideal for a wide range of **component assembly** and **welding repair applications** including plastic injection molds, dies and tooling repair, complex electronic components, high precision industrial assemblies, pressure sensitive hermetic laser sealing, and other unique industrial applications.

The **benefits** of **FiberStar** laser technology is that very little heat is transferred from the weld point allowing users to easily weld **<0.025mm** from complex, heat sensitive, intricate parts while providing unparalleled **pulse stability of < +/- 1%**.



LASERSTAR.NET

MOTIONFX



LASERSTAR.NET



**LASERSTAR
ACADEMY**

LASERSTARACADEMY.COM



LASERSTARTV

LASERSTAR.TV

LASERSTAR TECHNOLOGIES CORPORATION

2461 Orlando Central Parkway Orlando, Florida 32809 USA

Phone: +1-407-248-1142 ★ Email: sales@laserstar.net